



SAN JUAN COUNTY PUBLIC WORKS

CALL FOR BIDS MAINTENANCE MATERIALS – AGGREGATES 2010-2011 SAN JUAN COUNTY

ADDENDUM #1

SPECIFICATIONS

3/8" coverstone shall meet the 2010 WSDOT specifications for 3/8"-No. 10 (section 9-03.4(2)). The gradation is provided below for convenience

Additionally, the material must be **WASHED** and pass the Static Stripping Test.

<u>Crushed Screening</u>	<u>Percent Passing</u>
-	3/8" - U.S. No. 10
1" square	---
3/4" square	---
5/8" square	---
1/2" square	100
3/8" square	90-100
U.S. No. 4	0-20
U.S. No. 10	0-5
U.S. No. 200	0-1.5
% fracture by weight, min.	90
Sand equivalent, min.	N/A
Flat and Elongated Particles	0
Static stripping test	Pass

THIS PAGE MUST BE SUBMITTED WITH BID PACKAGE.



SAN JUAN COUNTY PUBLIC WORKS

CALL FOR BIDS

MAINTENANCE MATERIALS – AGGREGATES 2010-2011

SAN JUAN COUNTY

Due Date: Tuesday, January 19, 2010; 1:30pm

Additional specification packets are available at:
San Juan County Public Works Department,
915 Spring Street
PO Box 729
Friday Harbor, WA 98250.
Phone (360) 370-0500 or
suen@sjcpublishing.org or
<http://www.co.san-juan.wa.us/publicworks/index.html>

Published: January 6 and 13
Seattle Daily Journal of Commerce:
The Journal of the San Juan Islands
Islands Weekly
Sounder

**SAN JUAN COUNTY
FRIDAY HARBOR, WASHINGTON**

Call for Bids for Maintenance Materials – 2010 - 2011

Sealed Bids will be received and publicly opened by the County Administrator in the **San Juan County Council Hearing Room, 55 2nd St N, 1st Floor, Friday Harbor, Washington**, on **Tuesday, January 19, 2010 at 1:30pm** or as soon thereafter as possible, for the following products for San Juan County:

Aggregates

The purpose of this Call for Bids is to solicit bids for the procurement of Maintenance Materials, needed by San Juan County, for use during the period of February 1, 2010 through January 31, 2011. As per RCW 36.32.256, the County reserves the right to award the bid to more than one vendor, per item, when hauling distance is a factor.

Each of the four materials listed could be supplied by different vendors to different locations depending on the project. A vendor may bid on any one material or all four. This is not strictly a lowest bid process.

A purchasing contract, or a series of contracts, will be entered into for purchases of any or all bid items represented in this call for bids. The County Representative, when making purchases, will consider Price, Quality, Availability, and Transportation Costs of the product. San Juan County requires materials of the highest quality available. The County reserves the right to reject any or all offers and to waive informalities and minor irregularities in offers.

The quantities listed in the solicitation represent the County's current estimated requirements. The County will be neither obligated by nor restricted to the quantity(s) indicated.

All prices listed shall be shown as FOB the supplier's location.

A 5% Bid Bond, based on the value of the minimum quantities of each item bid upon, shall accompany this call for bids.

The successful bidder will be required to grant, on demand, access to their facilities by a County Representative for the purpose of collecting material samples for testing.

Sealed bid envelopes must be clearly marked on the outside, **"Call for Bids for Maintenance Materials, to be opened at 1:30pm, January 19, 2010"** and must be delivered to San Juan County Council Clerk, Friday Harbor office, prior to bid opening time.

BIDS RECEIVED AND NOT SO MARKED WILL NOT BE CONSIDERED.

Mailing Address: **San Juan County Council Clerk
55 2nd Ave N., 1st Floor
350 Court St #1
Friday Harbor, WA. 98250**

QUESTIONS? Contact Sue Nielsen, Procurement Specialist, 360/370-0527, suen@sjcpublicworks.org.

Vendors with materials to sell to San Juan County are requested to fill in the appropriate attached bid requests. Please P R I N T all of the relevant information. Feel free to attach an additional price list on products that you have available that may interest the County.

**SAN JUAN COUNTY
FRIDAY HARBOR, WASHINGTON**

Item 1: Aggregate Products

The County expects to purchase various quantities of the following Aggregate Products, for use during the proposed time period. Products offered are required to conform to specifications referenced in the Standard Specifications for Road, Bridge, and Municipal Construction, 2010 edition, unless otherwise indicated below. Prices will be quoted based on Customer Pickup of the product. Please include your standard price list, if applicable, for other available products. Use additional sheets if you have more than one site location that the County can purchase from. All prices will be in US tons. Do NOT include Sales Tax in the prices listed

Product	Location of Quarry	Min/Max Tons Purchase/Yr.	Loaded Product Price/Ton	Weight Tons/CY
3/8" Coverstone (washed) Standard Specs 9-03.4 With modified gradation as attached	_____	1000/8000	\$ _____	_____
5/8" Coverstone (washed) Standard Specs 9-03.4	_____	100/2000	\$ _____	_____
Crushed Topcourse Standard Specs 9-03.9(3)	_____	1000/5000	\$ _____	_____
Crushed Ballast Standard Specs 9-03.9(1)	_____	500/2000	\$ _____	_____

Bidder will submit a current gradation and dry weight analysis for each product bid upon. This gradation will be considered current if dated within the last two years.

Please include a full product list with pricing.

NAME of COMPANY: _____

MAILING ADDRESS: _____

CONTACT PERSON: _____ **Email:** _____

SIGNATURE: _____

UBI# _____ **INDUSTRIAL INS #** _____

TELEPHONE NUMBER: _____ **FAX NUMBER:** _____

EMAIL ADDRESS: _____

San Juan County Public Works 3/8" Coverstone Specifications

<u>Crushed Screening</u>	<u>Percent Passing</u>
-	<u>3/8" - U.S. No. 10</u>
<u>1" square</u>	<u>---</u>
<u>3/4" square</u>	<u>---</u>
<u>5/8" square</u>	<u>---</u>
<u>1/2" square</u>	<u>100</u>
<u>3/8" square</u>	<u>90-100</u>
<u>U.S. No. 4</u>	<u>30-56</u>
<u>U.S. No. 10</u>	<u>0-10</u>
<u>U.S. No. 200</u>	<u>0-1</u>
<u>% fracture by weight, min.</u>	<u>75</u>
<u>Sand equivalent, min.</u>	<u>N/A</u>
<u>Flat and Elongated Particles</u>	<u>0</u>
<u>Static stripping test</u>	<u>Pass</u>

The fracture requirement shall be at least one fractured face and will apply to material retained on each specification sieve size No.10 and above if that sieve retains more than 5 percent of the total sample.

The finished product shall be **washed**, clean, uniform in quality, and free from wood, bark, roots, and other deleterious materials.

Crushed screening shall be substantially free from adherent coatings. The presence of a thin, firmly adhering film on weathered rock shall not be considered as coating unless it exists on more than 50 percent of the surface area of any size between successive laboratory sieves.

The portion of aggregate for bituminous surface treatment retained on a U.S. No. 4 sieve shall not contain more than 0.1 percent deleterious materials by weight.